SHEEP HOCK and TONGUE BONE CUTTER Models 525-1 and 525-TB



The Jarvis Models 525-1 and 525-TB - hydraulic powered hock and tongue bone cutter for sheep.

- The 525-1 and 525-TB are best suited for sheep hock and tongue bone cutting. The Model 525-1 is also suitable for beef tail removal and poultry neck cutting.
- Compact for easy maneuverability; robust for long, trouble-free operation.
- Super fast cutting cycle combined with high cutting force means high performance for the most demanding applications.
- Dual trigger controls for operator safety.
- Constructed from corrosion resistant materials for optimum hygiene.
- Meets national and international requirements for hygiene and safety.





SHEEP HOCK and TONGUE BONE CUTTER Models 525-1 and 525-TB

Specifications			
Drive			Hydraulic
Models 525-1 and 525-T	В		
Capacity			720 / hour
Cutting Cycle Time			0.6 sec
Cutting Force		1425 lbf	6.34 kN
Control Handle			
Pneumatic Single / Dual Trigger		100 psi	6.9 bar
Pneumatic Dual Anti-tie Down		50 psi	3.4 bar
Blade Opening			
525-1		1.5 in	38.1 mm
525-TB		1.73 in	43.9 mm
Overall Length			
525-1		15.3 in	389 mm
525-TB		13.3 in	338 mm
Weight		9 lbs	4.1 kg
Hydraulic Power Unit			
Motor Power		5 hp	3729 W
· · · · · · · · · · · · · · · · · · ·		30 V, 3 phase, 60 Hz and 50 Hz available	
Hose Length		16 ft	4.9 m
Oil Capacity		20 gal	76 L
Overall Dimensions (I x w x h)		31.8 x 25.1 x 29.9 in	808 x 638 x 759 mm
Weight		250 lbs	113 kg
Oil Viscosity at 100° F / 4	0° C	200 SUS	46 ISO
Equipment Selection and Accessories			Order Number
Model 525-1	Sing	le Acting Dual Triggers	4025077
	Single Acting One Trigger ("CE" version)		4025078
	Dou	ble Acting Dual Trigger	4025107
Model 525-TB	Doub	le Acting Dual Triggers	4025099
Hydraulic Power Unit	460 / 230 V, 3 phase, 60 Hz		4027293
	440 / 415 / 380 / 220 V, 3 phase, 50 Hz		4027214
Balancer			4042044
Blade			
525-1			1023412
525-TB			1023561



Products for the meat and poultry industry