

TS200S Tray sealing machine

Technical data sheet

Small, fast packaging professional for trays

The TS200S tray sealing machine is a table-top model for sealing various tray materials and sizes. It offers a professional solution for the manual packaging of a wide range of products in trays. This packaging machine can be connected to a conventional domestic socket and is thus simple to use. In addition, the device is compact, easy to operate and clean, and very service-friendly.



Facts

External dimensions	800 x 702 x 712 mm *
Max. tray dimensions	
Single	325 x 265 x 100 mm *
Double	147 x 204 x 100 mm *
Machine cycle	
	Vacuum/gas up to 3 cycles/min
	Sealing up to 5 cycles/min
Vacuum pump	8 m ³ /h
Weight	77 kg
Automated process, standard	evacuation – re-gassing – sealing and cutting
Electrical connection	230 V/1/50 Hz/1.6 kW **
Compressed air	no
MAP gas connection:	
Operating pressure	1 bar
Hose connection	ID 6 mm
Version with oxygen pump	optional
Automatic intake / drawer	no
Tray lifting	no
Skin function	no
Trolley	Accessory
incl. cylinder holder	

* Width x depth x height

** Voltage variants on request
Subject to technical changes



Maximum tray dimensions



Other dimensions/shapes on request. Special shapes also possible: round, oval, subdivided, sealed, etc.



Options & accessories

1. Version for oxygen application (>21%)
2. Tool making for various trays
3. Trolley
4. Add-on base with bag holder
5. Add-on base with shelf
6. Small ramp for easy replacement of the gas cylinder
7. Pressure regulator with hose and open-end spanner

